


Model No.	AD-1280HP
	
RH Control Range	25%-55% RH
Recovery Time	Recovers to original RH within 2 hours after accessing door for 30 seconds or less.
External Dimension	W1200 x H1950 x D650 mm
Internal Dimension	W1140 x H1720 x D596mm
Capacity	1326 litres
Cabinet Material	SPCC, and powder coated
Cabinet Color	Biege/Cream
Shelves	5pcs of metal shelves (Height adjustable)
Loading Capacity of Shelf	100kg
Doors	6 doors with locks
Core Units	In the event of a power failure, dehumidification is maintained with doors closed
Voltage	220V
Hygrometer	3rd Party monitor system, Japanese Analog Thermal Hygrometer
Hygrometer measuring range & accuracy	0-95%RH \pm 3%RH 0-50°C \pm 0.5°C
Indicator	Have power indicator in the cabinet and operating indicator on core units
Ave Power Consumption	48w
Dual RH Sensor Design	Built-in independent sensors in the drying system and hygrometer provides RH monitoring independent of each other
Brand	Eureka
Country of Manufacture	Taiwan



100KG



Loading Cap per shelf



Comes with castor wheels and levelling legs



- 4 Dehumidifiers / Dry Unit
- Adjustable Humidity Range of 25%-55% RH



Analog Thermal Hygrometer
Accuracy \pm 5%
Made in Japan

For more information, contact us at enquiry@drycabinets.com.sg or simply give us a call at 67491812