


| | |
|---------------------------------------|---|
| Model No. | TUS-2003 |
| |  |
| RH Control Range | 10%-50% RH |
| Fast Recovery Time | Recovers to $\leq 20\%$ RH within 2 hours after accessing door for 30 seconds or less. |
| External Dimension | W1200 x H1950 x D714mm |
| Internal Dimension | W1100 x H1700 x D610mm |
| Capacity | 1329 Liter |
| Cabinets | Anti-static Paint on Body and Shelves Anti-Static Glass (Thickness:3mm), Anti-static Caster / Stands, 1 M Ω Ground Wire |
| Cabinet Material | Made by SECC/ Thickness:1mm |
| Cabinet Color | Grey |
| Anti Static Painting | Surface Resistivity $\leq 100k\Omega$ |
| Shelves | 5 pcs of metal shelves with anti-static painting (Height adjustable) |
| Loading Capacity of Shelf | 100kg |
| Doors | 6 doors with locks |
| Core Units | In the event of a power failure, dehumidification is maintained with doors closed |
| Voltage | 220V |
| Hygrometer | 3rd Party monitor system, TESTO digital thermal hygrometer |
| Hygrometer measuring range & accuracy | 0-95%RH $\pm 3\%$ RH 0-50°C $\pm 0.5^\circ$ C |
| Indicator | Have power indicator in the cabinet and operating indicator on core units |
| Ave Power Consumption | 44w |
| Dual RH Sensor Design | Built-in independent sensors in the drying system and hygrometer provides RH monitoring independent of each other |
| Brand | Eureka |
| Country of Manufacture | Taiwan |

For more information, contact us at enquiry@drycabinets.com.sg or simply give us a call at 67491812