


Model No.	XDC-503
	
RH Control Range	≤ 5% RH
Fast Recovery Time	Down to ≤ 5% RH within 30 mins after open a door in 30 sec and close it. (Empty Cabinet Testing)
External Dimension	W880 x H930 x D584mm
Internal Dimension	W830 x H790 x D480mm
Capacity	376 Liter
Cabinets	Anti-static Paint on Body and Shelves Anti-Static Glass (Thickness:3mm), Anti-static Stands 1 M Ω Ground Wire
Cabinet Material	Made by SECC/ Thickness:1mm
Cabinet Color	Grey
Anti Static Painting	Surface Resistivity ≤100kΩ
Shelves	3pcs of metal shelves with anti-static painting (Height adjustable)
Loading Capacity of Shelf	50kg
Doors	2 doors with locks
Core Units	In the event of a power failure, dehumidification is maintained with doors closed
Voltage	220V
Hygrometer	3rd Party monitor system, German Digital TESTO Thermal Hygrometer
Hygrometer measuring range & accuracy	0-95%RH ±3%RH 0-50°C±0.5°C
Indicator	Have power indicator in the cabinet and operating indicator on core units
Ave Power Consumption	100w
Dual RH Sensor Design	Built-in independent sensors in the drying system and hygrometer provides RH monitoring independent of each other
Brand	Eureka
Country of Manufacture	Taiwan

For more information, contact us at enquiry@drycabinets.com.sg or simply give us a call at 67491812