


<b>Model No.</b>	<b>MD-5250</b>
	
<b>RH Control Range</b>	25%-55% RH
<b>External Dimension</b>	W530 x H1060 x D470 mm
<b>Internal Dimension</b>	W490 x H950 x D343 mm
<b>Capacity</b>	239 Liter
<b>Cabinet Material</b>	SPCC, and powder coated
<b>Cabinet Color</b>	White
<b>Drawers</b>	5 Lockable Drawers
<b>Loading Capacity of Drawers</b>	40kg
<b>Core Units</b>	In the event of a power failure, dehumidification is maintained with doors closed
<b>Voltage</b>	220V
<b>Hygrometer</b>	3rd Party monitor system, Japanese Analog Thermal Hygrometer
<b>Hygrometer measuring range &amp; accuracy</b>	0-95%RH ±3%RH 0-50°C±0.5°C
<b>Indicator</b>	Have power indicator in the cabinet and operating indicator on core units
<b>Ave Power Consumption</b>	12w
<b>Dual RH Sensor Design</b>	Built-in independent sensors in the drying system and hygrometer provides RH monitoring independent of each other
<b>Brand</b>	Eureka
<b>Country of Manufacture</b>	Taiwan

For more information, contact us at [enquiry@drycabinets.com.sg](mailto:enquiry@drycabinets.com.sg)  
or simply give us a call at 67491812