


<b>Model No.</b>	<b>TD-101</b>
	
<b>RH Control Range</b>	≤ 20% RH
<b>Fast Recovery Time</b>	Recovers to ≤ 20% RH within 30 minutes after accessing door for 30 seconds or less.
<b>External Dimension</b>	W400 x H692 x D437mm
<b>Internal Dimension</b>	W360 x H597 x D357mm
<b>Capacity</b>	93 Liter
<b>Cabinets</b>	Anti-static Glass, Anti-static Paint on Body and Shelves, Anti-static Caster / Stands, 1 M Ω Ground Wire93
<b>Cabinet Material</b>	Made by SECC/ Thickness:1mm
<b>Cabinet Color</b>	Grey
<b>Anti Static Painting</b>	Surface Resistivity ≤100kΩ
<b>Shelves</b>	2pcs of metal shelves with anti-static painting (Height adjustable)
<b>Loading Capacity of Shelf</b>	20kg
<b>Doors</b>	1 door with locks
<b>Core Units</b>	In the event of a power failure, dehumidification is maintained with doors closed
<b>Voltage</b>	220V
<b>Hygrometer</b>	3rd Party monitor system, TESTO digital thermal hygrometer
<b>Hygrometer measuring range &amp; accuracy</b>	0-95%RH ±3%RH 0-50°C±0.5°C
<b>Indicator</b>	Have power indicator in the cabinet and operating indicator on core units
<b>Ave Power Consumption</b>	20w
<b>Dual RH Sensor Design</b>	Built-in independent sensors in the drying system and hygrometer provides RH monitoring independent of each other
<b>Brand</b>	Eureka
<b>Country of Manufacture</b>	Taiwan

For more information, contact us at enquiry@drycabinets.com.sg  
or simply give us a call at 67491812